

DECLARATION OF PERFORMANCE N. CPR-DE1/0134.1

- 1) Unique identification code of the product-type: **MAPEFILL 130 WT**
- 2) Intended use: **Anchoring cementitious mortar for strengthening concrete by installing reinforcing steel (rebars) in building and civil engineering works**
- 3) Manufacturer: **MAPEI GmbH – Schwarzer Weg 3 – 39356 Weferlingen (Germany)**
www.mapei.de
- 4) Systems of AVCP: **System 2+**
System 4 (for reaction to fire)
- 5) Harmonized standards: **EN 1504-6:2006**

Notified bodies: **Kiwa Polymer Institut GmbH, N. 1119**

- 6) Performances declared:

Essential characteristics	Performances
Pull-out strength: Chloride ion content: Reaction to fire: Dangerous substances:	Displacement $\leq 0,6$ mm at a load of 75 kN $\leq 0,05$ % Class A1 NPD

- 7) Appropriate Technical Documentation: **included, as long as needed, in the technical dossier stored by the manufacturer. Reaction to fire class declared without the need for testing according to the Decision of the Commission 96/603/EC and following amendments.**
Organic material <1 % by mass

The performance of the product identified above is in conformity with the set of declared performances.

This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

Frank Sommer - Mapei GmbH, Leiter Qualitätsmanagement

Weferlingen, 14/10/2021

Mapei GmbH

 Frank Sommer | Quality Management

REACH-information: the information referred to Article 31 or, as appropriate, to Article 33 of the REACH Regulation (EC) No 1907/2006 and following amendments are indicated in the Safety Data Sheet that MAPEI makes available on the website along with the current Declaration of Performance.

DoP in Pdf format are available in the Mapei website.

Revision 0 notes:	First issue
-------------------	-------------

MAPEFILL 130 WT
CE MARKING
Annex to DoP N. CPR-DE1/0134.1

 1119	 MAPEI GmbH Schwarzer Weg 3 – 39356 Weferlingen (Germany) www.mapei.de
21 CPR-DE1/0134.1 EN 1504-6 MAPEFILL 130 WT <i>Anchoring cementitious mortar for strengthening concrete by installing reinforcing steel (rebars) in building and civil engineering works</i>	
Pull-out strength: Chloride ion content: Reaction to fire: Dangerous substances:	Displacement ≤ 0,6 mm at a load of 75 kN ≤ 0,05 % Class A1 NPD

Note:

MAPEI supplies the current annex along with the DoP to make the consultancy of the CE marking easier for the international clients. The enclosed CE marking can be slightly different compared to the one printed on the relevant packaging or documentation because of:

- NPD (No Performance Determined) values can be omitted by the CE marking,
- graphic adaptations due to lack of space on the packaging or printing methods used,
- different language (the same packaging can be shared by several countries),
- the product is already in stock when the updating of the CE marking is implemented,
- printing mistakes.