

DECLARATION OF PERFORMANCE N. CPR-IT1/0658

- 1) Unique identification code of the product-type: **MAPEFIBRE AT 06 FP**
- 2) Intended uses: **Mono-filamented polypropylene fibres (Class Ia, length 6 mm, diameter 0,018 mm) for other uses in concrete, mortar or grout**
- 3) Manufacturer: **MAPEI S.p.A. – Via Cafiero, 22 – 20158 Milan – Italy - www.mapei.it**
- 4) Systems of AVCP: **System 3**
- 5) Harmonized standards: **EN 14889-2:2006**

Notified bodies: **the notified laboratory Tecnoprove S.r.l., N. 0925, carried out the assessment of the performance on the basis of testing on samples taken by the manufacturer.**

- 6) Performances declared:

Essential characteristics	Performances
Tensile properties:	
- tenacity:	38 cN/tex
Effect on consistence of concrete:	
- increase of Vebè time with 2 kg/m ³ fibres:	2,9 s
Release of dangerous substances:	NPD

- 7) REACH information: this is an article in accordance with Article 3 of the REACH Regulation (EC) no. 1907/2006 and pursuant to Article 31 and 33 of the above-mentioned Regulation does not require any Safety Data Sheet. While using the product, pay attention to the recommendations written in the Technical Data Sheet and to the safety requirements laid down in the workplace.

The performance of the product identified above is in conformity with the set of declared performances.

This declaration of performance is issued, in accordance with Regulation (EU) no. 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by **Lorenzo Martino – Corporate Quality Management**

Milan, 10/06/2020

..... 

DoP in Pdf format are available in the Mapei website.

Revision 1 notes:	Renewed product
-------------------	-----------------

MAPEFIBRE AT 06 FP
CE MARKING
Annex to DoP N. CPR-IT1/0658



 0925	 Via Cafiero, 22 – 20158 Milano (Italy) www.mapei.it
17 CPR-IT1/0658 EN 14889-2 MAPEFIBRE AT 06 FP <i>Mono-filamented polypropylene fibres (Class Ia, length 6 mm, diameter 0,018 mm) for other uses in concrete, mortar or grout</i>	
Tensile properties: - tenacity: 38 cN/tex Effect on consistence of concrete: - increase of Vebè time with 2 kg/m³ fibres: 2,9 s Release of dangerous substances: NPD	

Note:

MAPEI supplies the current annex along with the DoP to make the consultancy of the CE marking easier for the international clients. The enclosed CE marking can be slightly different compared to the one printed on the relevant packaging or documentation because of:

- graphic adaptations due to lack of space on the packaging or printing methods used,
- different language (the same packaging can be shared by several countries),
- the product is already in stock when the updating of the CE marking is implemented,
- printing mistakes.